


## LUMINAIRE PHOTOMETRIC TEST REPORT


NAME: LED High Bay	TYPE:	WEIGHT:
DIM.: $\varnothing 260 \times H150 \text{mm}$	SPEC.:	SERIAL No.:
MFR.:	SUR.: $\varphi 0.26$	PROTECTION ANGLE:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 170.05 lm/W			
MODEL	UFO-100W-120D	Imax(cd)	5706	S/MH(C0/180)	1.32
NOMINAL POWER(W)	100	LOR(%)	100.0	S/MH(C90/270)	1.32
RATED VOLTAGE(V)	232	TOTAL FLUX(lm)	17005	$\eta$ UP,DN(C0-180)	0.0,51.1
NOMINAL FLUX(lm)	17005.2	CIE CLASS	DIRECT	$\eta$ UP,DN(C180-360)	0.0,48.9
LAMPS INSIDE	1	$\eta$ up(%)	0.0	CIBSE SHR NOM	1.50
TEST VOLTAGE(V)	231.2	$\eta$ down(%)	100.0	CIBSE SHR MAX	1.50

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



C Range: 0 - 360DEG  
C Interval: 90.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:chen xue chang  
Test Date:2022-04-12

$\gamma$  Range: 0 - 90DEG  
 $\gamma$  Interval: 1.0DEG  
Test System:EVERFINE GO-2000B\_V1 SYSTEM V2.0.269  
Humidity:65.0%  
Test Distance:6.900m [K=1.0000]  
Remarks:

## ZONAL FLUX DIAGRAM

## ZONAL FLUX DIAGRAM:

$\gamma$	C0	C90	C180	C270					$\gamma$	$\Phi$ zone	$\Phi$ total	%lum, lamp
10	5625	5607	5586	5588					0- 10	538.5	538.5	3.17,3.17
20	5404	5412	5364	5342					10- 20	1554	2093	12.3,12.3
30	4990	5022	4936	4901					20- 30	2393	4485	26.4,26.4
40	4462	4468	4358	4334					30- 40	2949	7435	43.7,43.7
50	3747	3767	3631	3605					40- 50	3145	10580	62.2,62.2
60	2893	2921	2762	2736					50- 60	2931	13511	79.5,79.5
70	1801	1840	1635	1607					60- 70	2284	15795	92.9,92.9
80	438.6	448.5	326.7	311.1					70- 80	1072	16867	99.2,99.2
90	71.98	71.95	52.84	52.74					80- 90	137.9	17005	100,100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		


C Range: 0 - 360DEG  
 C Interval: 90.0DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:chen xue chang  
 Test Date:2022-04-12

$\gamma$  Range: 0 - 90DEG  
 $\gamma$  Interval: 1.0DEG  
 Test System:EVERFINE GO-2000B\_V1 SYSTEM V2.0.269  
 Humidity:65.0%  
 Test Distance:6.900m [K=1.0000]  
 Remarks:

## CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

NAME: LED High Bay	TYPE:	WEIGHT:
DIM.: $\phi 260 \times H150\text{mm}$	SPEC.:	SERIAL No.:
MFR.:	SUR.: $\phi 0.26$	PROTECTION ANGLE:

$\rho_{cc}$	80%			70%			50%			30%			10%			0
$\rho_w$	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
$\rho_{fc}$	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio			Coefficients of Utilization(CU)												
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.11	1.11	1.11	1.06	1.06	1.06	1.02	1.02	1.02	1.00
1.0	1.04	1.00	.96	1.02	.98	.95	.98	.95	.92	.94	.91	.89	.90	.88	.86	.84
2.0	.91	.84	.78	.89	.83	.77	.85	.80	.76	.82	.78	.74	.79	.75	.72	.70
3.0	.80	.71	.65	.78	.70	.64	.75	.68	.63	.72	.67	.62	.70	.65	.61	.59
4.0	.70	.61	.55	.69	.61	.54	.66	.59	.54	.64	.58	.53	.62	.57	.52	.50
5.0	.63	.54	.47	.61	.53	.47	.59	.52	.46	.57	.51	.46	.56	.50	.45	.43
6.0	.56	.47	.41	.55	.47	.41	.53	.46	.40	.52	.45	.40	.50	.44	.39	.37
7.0	.51	.42	.36	.50	.42	.36	.48	.41	.35	.47	.40	.35	.46	.40	.35	.33
8.0	.46	.38	.32	.46	.37	.32	.44	.37	.32	.43	.36	.31	.42	.36	.31	.29
9.0	.42	.34	.29	.42	.34	.28	.41	.33	.28	.40	.33	.28	.39	.32	.28	.26
10.0	.39	.31	.26	.39	.31	.26	.38	.31	.26	.37	.30	.26	.36	.30	.25	.24



C Range: 0 - 360DEG  
 C Interval: 90.0DEG  
 Test Speed: HIGH  
 Temperature: 25.3DEG  
 Operators: chen xue chang  
 Test Date: 2022-04-12

$\gamma$  Range: 0 - 90DEG  
 $\gamma$  Interval: 1.0DEG  
 Test System: EVERFINE GO-2000B\_V1 SYSTEM V2.0.269  
 Humidity: 65.0%  
 Test Distance: 6.900m [K=1.0000]  
 Remarks:

## WEC AND CCEC

NAME: LED High Bay	TYPE:	WEIGHT:
DIM.: $\phi 260 \times H150\text{mm}$	SPEC.:	SERIAL No.:
MFR.:	SUR.: $\phi 0.26$	PROTECTION ANGLE:

$\rho_{cc}$	80%			70%			50%			30%			10%			0	
$\rho_w$	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
$\rho_{fc}$	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients(WEC)										
0.0																	
1.0	.300	.170	.054	.293	.167	.053	.279	.160	.051	.267	.154	.049	.256	.148	.048		
2.0	.288	.158	.048	.282	.155	.048	.270	.150	.047	.259	.145	.045	.249	.141	.044		
3.0	.269	.143	.043	.263	.141	.042	.253	.137	.042	.243	.133	.041	.234	.130	.040		
4.0	.249	.129	.038	.244	.128	.038	.235	.125	.037	.227	.122	.037	.219	.119	.036		
5.0	.231	.118	.034	.227	.116	.034	.218	.114	.033	.211	.111	.033	.204	.109	.033		
6.0	.214	.107	.031	.211	.106	.031	.203	.104	.030	.196	.102	.030	.190	.100	.030		
7.0	.200	.099	.028	.196	.098	.028	.190	.096	.028	.184	.094	.027	.178	.092	.027		
8.0	.187	.091	.026	.184	.090	.026	.178	.089	.025	.172	.087	.025	.167	.086	.025		
9.0	.175	.085	.024	.172	.084	.024	.167	.083	.023	.162	.081	.023	.157	.080	.023		
10.0	.164	.079	.022	.162	.078	.022	.157	.077	.022	.153	.076	.022	.149	.075	.021		

$\rho_{cc}$	80%			70%			50%			30%			10%			0
$\rho_w$	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
$\rho_{fc}$	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients(CCEC)									
0.0	.190	.190	.190	.163	.163	.163	.111	.111	.111	.064	.064	.064	.020	.020	.020	
1.0	.180	.156	.135	.154	.134	.116	.105	.092	.080	.061	.053	.047	.019	.017	.015	
2.0	.172	.132	.098	.147	.114	.085	.101	.079	.059	.058	.046	.035	.019	.015	.011	
3.0	.164	.114	.074	.141	.099	.065	.097	.068	.045	.056	.040	.027	.018	.013	.009	
4.0	.157	.101	.058	.135	.087	.051	.093	.061	.036	.054	.036	.021	.017	.012	.007	
5.0	.150	.091	.047	.128	.078	.041	.088	.055	.029	.051	.032	.017	.017	.010	.006	
6.0	.143	.082	.039	.122	.071	.034	.084	.050	.024	.049	.029	.014	.016	.010	.005	
7.0	.136	.075	.033	.117	.065	.029	.081	.046	.020	.047	.027	.012	.015	.009	.004	
8.0	.129	.070	.029	.111	.060	.025	.077	.042	.018	.045	.025	.011	.014	.008	.003	
9.0	.123	.065	.025	.106	.056	.022	.074	.039	.016	.043	.023	.009	.014	.008	.003	
10.0	.118	.060	.022	.101	.052	.019	.070	.037	.014	.041	.022	.008	.013	.007	.003	

C Range: 0 - 360DEG  
 C Interval: 90.0DEG  
 Test Speed: HIGH  
 Temperature: 25.3DEG  
 Operators: chen xue chang  
 Test Date: 2022-04-12

$\gamma$  Range: 0 - 90DEG  
 $\gamma$  Interval: 1.0DEG  
 Test System: EVERFINE GO-2000B\_V1 SYSTEM V2.0.269  
 Humidity: 65.0%  
 Test Distance: 6.900m [K=1.0000]  
 Remarks:

### Uncorrected UGR Table

NAME: LED High Bay					TYPE:					WEIGHT:				
DIM.: $\varnothing 260 \times H150\text{mm}$					SPEC.:					SERIAL No.:				
MFR.:					SUR.: $\varphi 0.26$					PROTECTION ANGLE:				
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3				
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3				
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2				
Room dimensions					Viewed crosswise					Viewed endwise				
x = 2H y = 2H					29.5	31.0	29.8	31.2	31.4	29.5	31.1	29.8	31.3	31.5
3H					31.1	32.5	31.4	32.8	33.0	31.2	32.6	31.5	32.8	33.1
4H					31.6	32.9	31.9	33.2	33.4	31.7	33.0	32.0	33.3	33.5
6H					31.8	33.0	32.1	33.3	33.6	31.8	33.1	32.2	33.4	33.7
8H					31.8	33.0	32.1	33.3	33.5	31.8	33.1	32.2	33.3	33.6
12H					31.7	32.9	32.1	33.2	33.5	31.8	33.0	32.1	33.3	33.6
4H 2H					30.2	31.5	30.5	31.8	32.0	30.2	31.5	30.5	31.8	32.1
3H					31.9	33.1	32.3	33.4	33.7	32.0	33.2	32.3	33.4	33.8
4H					32.5	33.6	32.9	33.9	34.2	32.6	33.6	32.9	34.0	34.3
6H					32.7	33.7	33.1	34.0	34.4	32.8	33.7	33.2	34.1	34.5
8H					32.7	33.6	33.1	34.0	34.4	32.8	33.7	33.2	34.1	34.4
12H					32.7	33.5	33.1	33.9	34.3	32.8	33.6	33.2	34.0	34.4
8H 4H					32.7	33.5	33.1	33.9	34.3	32.7	33.6	33.1	34.0	34.4
6H					33.0	33.7	33.4	34.1	34.5	33.0	33.8	33.5	34.2	34.6
8H					33.0	33.6	33.5	34.1	34.5	33.1	33.7	33.5	34.1	34.6
12H					33.0	33.5	33.5	34.0	34.5	33.1	33.6	33.5	34.1	34.5
12H 4H					32.6	33.5	33.1	33.8	34.2	32.7	33.5	33.1	33.9	34.3
6H					33.0	33.6	33.4	34.0	34.5	33.0	33.7	33.5	34.1	34.5
8H					33.0	33.6	33.5	34.0	34.5	33.1	33.6	33.6	34.1	34.6
Variations with the observer position at spacings:														
S = 1.0H					+ 0.2 / - 0.2					+ 0.1 / - 0.2				
1.5H					+ 0.2 / - 0.3					+ 0.2 / - 0.3				
2.0H					+ 0.2 / - 0.3					+ 0.2 / - 0.3				

CIE Pub.117 Corrected 17005 lm Total Lamp Luminous Flux. (8log(F/F0) = 9.8)

C Range: 0 - 360DEG  
C Interval: 90.0DEG  
Test Speed: HIGH  
Temperature: 25.3DEG  
Operators: chen xue chang  
Test Date: 2022-04-12

$\gamma$  Range: 0 - 90DEG  
 $\gamma$  Interval: 1.0DEG  
Test System: EVERFINE GO-2000B\_V1 SYSTEM V2.0.269  
Humidity: 65.0%  
Test Distance: 6.900m [K=1.0000]  
Remarks:


```

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.269
Humidity:65.0%
Test Distance:6.900m [K=1.0000]
Remarks:

```

## ISOCANDELA DIAGRAM

NAME: LED High Bay	TYPE:	WEIGHT:
DIM.: $\phi 260 \times H150\text{mm}$	SPEC.:	SERIAL No.:
MFR.:	SUR.: $\phi 0.26$	PROTECTION ANGLE:




C Range: 0 - 360DEG  
C Interval: 90.0DEG  
Test Speed: HIGH  
Temperature: 25.3DEG  
Operators: chen xue chang  
Test Date: 2022-04-12

$\gamma$  Range: 0 - 90DEG  
 $\gamma$  Interval: 1.0DEG  
Test System: EVERFINE GO-2000B\_V1 SYSTEM V2.0.269  
Humidity: 65.0%  
Test Distance: 6.900m [K=1.0000]  
Remarks:

### AAI Figure

NAME: LED High Bay	TYPE:	WEIGHT:
DIM.: $\phi 260 \times H150\text{mm}$	SPEC.:	SERIAL No.:
MFR.:	SUR.: $\phi 0.26$	PROTECTION ANGLE:



Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.


C Range: 0 - 360DEG  
C Interval: 90.0DEG  
Test Speed: HIGH  
Temperature: 25.3DEG  
Operators: chen xue chang  
Test Date: 2022-04-12

$\gamma$  Range: 0 - 90DEG  
 $\gamma$  Interval: 1.0DEG  
Test System: EVERFINE GO-2000B\_V1 SYSTEM V2.0.269  
Humidity: 65.0%  
Test Distance: 6.900m [K=1.0000]  
Remarks:



## ISOLUX DIAGRAM


NAME: LED High Bay	TYPE:	WEIGHT:
DIM.: $\phi 260 \times H150\text{mm}$	SPEC.:	SERIAL No.:
MFR.:	SUR.: $\phi 0.26$	PROTECTION ANGLE:



C Range: 0 - 360DEG  
 C Interval: 90.0DEG  
 Test Speed: HIGH  
 Temperature: 25.3DEG  
 Operators: chen xue chang  
 Test Date: 2022-04-12

$\gamma$  Range: 0 - 90DEG  
 $\gamma$  Interval: 1.0DEG  
 Test System: EVERFINE GO-2000B\_V1 SYSTEM V2.0.269  
 Humidity: 65.0%  
 Test Distance: 6.900m [K=1.0000]  
 Remarks:

## Planar Illuminance Curve



C Range: 0 - 360DEG  
C Interval: 90.0DEG  
Test Speed: HIGH  
Temperature: 25.3DEG  
Operators: chen xue chang  
Test Date: 2022-04-12

$\gamma$  Range: 0 - 90DEG  
 $\gamma$  Interval: 1.0DEG  
Test System: EVERFINE GO-2000B\_V1 SYSTEM V2.0.269  
Humidity: 65.0%  
Test Distance: 6.900m [K=1.0000]  
Remarks:

```

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.269
Humidity:65.0%
Test Distance:6.900m [K=1.0000]
Remarks:

```