


LUMINAIRE PHOTOMETRIC TEST REPORT


NAME: LED High Bay	TYPE:	WEIGHT:
DIM.: $\varnothing 260 \times H150\text{mm}$	SPEC.:	SERIAL No.:
MFR.:	SUR.: $\varphi 0.26$	PROTECTION ANGLE:

DATA OF LAMP		PHOTOMETRIC DATA				Eff: 168.27 lm/W
MODEL	UFO-100W-90D	Imax(cd)	7912	S/MH(C0/180)	1.27	
NOMINAL POWER(W)	99.7	LOR(%)	100.0	S/MH(C90/270)	1.29	
RATED VOLTAGE(V)	232	TOTAL FLUX(lm)	16777	η UP,DN(C0-180)	0.0,50.5	
NOMINAL FLUX(lm)	16776.6	CIE CLASS	DIRECT	η UP,DN(C180-360)	0.0,49.5	
LAMPS INSIDE	1	η up(%)	0.0	CIBSE SHR NOM	1.25	
TEST VOLTAGE(V)	232.9	η down(%)	100.0	CIBSE SHR MAX	1.35	

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



C Range: 0 - 360DEG
C Interval: 90.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: chen xue chang
Test Date: 2022-04-12

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System: EVERFINE GO-2000B_V1 SYSTEM V2.0.269
Humidity: 65.0%
Test Distance: 7.100m [K=1.0000]
Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:

γ	C0	C90	C180	C270					γ	Φ zone	Φ total	%lum, lamp
10	7855	7892	7748	7664					0- 10	744.0	744.0	4.43,4.43
20	7783	7815	7711	7590					10- 20	2202	2946	17.6,17.6
30	7135	7148	7227	7335					20- 30	3482	6428	38.3,38.3
40	5186	5353	5145	5911					30- 40	4023	10451	62.3,62.3
50	2977	2869	2793	2836					40- 50	3126	13576	80.9,80.9
60	1545	1465	1322	1280					50- 60	1865	15442	92,92
70	609.0	605.6	500.7	459.5					60- 70	908.3	16350	97.5,97.5
80	180.0	195.1	119.2	87.03					70- 80	342.7	16693	99.5,99.5
90	61.53	60.85	49.78	49.64					80- 90	83.89	16777	100,100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		


C Range: 0 - 360DEG
 C Interval: 90.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:chen xue chang
 Test Date:2022-04-12

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.269
 Humidity:65.0%
 Test Distance:7.100m [K=1.0000]
 Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

NAME: LED High Bay	TYPE:	WEIGHT:
DIM.: $\varnothing 260 \times H150\text{mm}$	SPEC.:	SERIAL No.:
MFR.:	SUR.: $\varphi 0.26$	PROTECTION ANGLE:

ρ_{cc}	80%			70%			50%			30%			10%			0
ρ_w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
ρ_{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Coefficients of Utilization(CU)									
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.11	1.11	1.11	1.06	1.06	1.06	1.02	1.02	1.02	1.00
1.0	1.07	1.04	1.01	1.05	1.02	.99	1.01	.98	.96	.97	.95	.93	.94	.92	.91	.89
2.0	.96	.91	.86	.94	.89	.85	.91	.87	.83	.88	.84	.81	.85	.82	.80	.78
3.0	.87	.80	.74	.85	.79	.74	.82	.77	.72	.80	.75	.71	.77	.73	.70	.68
4.0	.78	.71	.65	.77	.70	.65	.75	.68	.64	.72	.67	.63	.70	.66	.62	.60
5.0	.71	.63	.57	.70	.62	.57	.68	.61	.56	.66	.60	.56	.64	.59	.55	.53
6.0	.65	.57	.51	.64	.56	.51	.62	.55	.50	.60	.54	.50	.59	.54	.50	.48
7.0	.59	.51	.46	.58	.51	.46	.57	.50	.45	.55	.49	.45	.54	.49	.45	.43
8.0	.54	.47	.41	.54	.46	.41	.52	.46	.41	.51	.45	.41	.50	.45	.41	.39
9.0	.50	.43	.38	.50	.42	.37	.48	.42	.37	.47	.41	.37	.46	.41	.37	.35
10.0	.46	.39	.34	.46	.39	.34	.45	.39	.34	.44	.38	.34	.43	.38	.34	.32



C Range: 0 - 360DEG
 C Interval: 90.0DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators: chen xue chang
 Test Date: 2022-04-12

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System: EVERFINE GO-2000B_V1 SYSTEM V2.0.269
 Humidity: 65.0%
 Test Distance: 7.100m [K=1.0000]
 Remarks:

WEC AND CCEC

NAME: LED High Bay	TYPE:	WEIGHT:
DIM.: $\phi 260 \times H150mm$	SPEC.:	SERIAL No.:
MFR.:	SUR.: $\phi 0.26$	PROTECTION ANGLE:

ρ_{cc}	80%			70%			50%			30%			10%			0	
ρ_w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
ρ_{fc}	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients(WEC)										
0.0																	
1.0	.243	.138	.044	.236	.135	.043	.223	.128	.041	.211	.122	.039	.200	.116	.037		
2.0	.235	.129	.040	.230	.126	.039	.218	.121	.038	.208	.117	.037	.198	.112	.035		
3.0	.224	.119	.036	.218	.117	.035	.209	.113	.034	.200	.109	.034	.191	.106	.033		
4.0	.211	.110	.032	.207	.108	.032	.198	.105	.031	.190	.102	.031	.182	.099	.030		
5.0	.199	.101	.029	.195	.100	.029	.187	.098	.029	.180	.095	.028	.174	.093	.028		
6.0	.188	.094	.027	.184	.093	.027	.177	.091	.026	.171	.089	.026	.165	.087	.026		
7.0	.177	.088	.025	.174	.087	.025	.168	.085	.024	.162	.083	.024	.157	.081	.024		
8.0	.167	.082	.023	.164	.081	.023	.159	.079	.023	.154	.078	.022	.149	.077	.022		
9.0	.158	.077	.021	.156	.076	.021	.151	.075	.021	.146	.073	.021	.142	.072	.021		
10.0	.150	.072	.020	.148	.071	.020	.143	.070	.020	.139	.069	.020	.135	.068	.020		

ρ_{cc}	80%			70%			50%			30%			10%			0
ρ_w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
ρ_{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients(CCEC)									
0.0	.190	.190	.190	.163	.163	.163	.111	.111	.111	.064	.064	.064	.020	.020	.020	
1.0	.176	.157	.140	.150	.135	.120	.103	.093	.083	.059	.054	.048	.019	.017	.016	
2.0	.165	.132	.105	.141	.114	.091	.097	.079	.063	.056	.046	.037	.018	.015	.012	
3.0	.156	.114	.081	.133	.098	.070	.092	.068	.049	.053	.040	.029	.017	.013	.009	
4.0	.147	.100	.064	.127	.087	.056	.087	.060	.039	.050	.035	.023	.016	.012	.008	
5.0	.140	.089	.052	.120	.077	.045	.083	.054	.032	.048	.032	.019	.015	.010	.006	
6.0	.133	.081	.043	.115	.070	.037	.079	.049	.026	.046	.029	.016	.015	.009	.005	
7.0	.127	.074	.036	.109	.064	.032	.076	.045	.022	.044	.026	.013	.014	.009	.004	
8.0	.121	.068	.031	.104	.059	.027	.072	.041	.019	.042	.024	.011	.014	.008	.004	
9.0	.116	.063	.027	.100	.055	.024	.069	.038	.017	.040	.023	.010	.013	.007	.003	
10.0	.111	.059	.024	.096	.051	.021	.066	.036	.015	.039	.021	.009	.013	.007	.003	

C Range: 0 - 360DEG
 C Interval: 90.0DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators: chen xue chang
 Test Date: 2022-04-12

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System: EVERFINE GO-2000B_V1 SYSTEM V2.0.269
 Humidity: 65.0%
 Test Distance: 7.100m [K=1.0000]
 Remarks:

Uncorrected UGR Table

NAME: LED High Bay					TYPE:					WEIGHT:				
DIM.: $\varnothing 260 \times H150\text{mm}$					SPEC.:					SERIAL No.:				
MFR.:					SUR.: $\varphi 0.26$					PROTECTION ANGLE:				
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3				
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3				
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2				
Room dimensions					Viewed crosswise					Viewed endwise				
x = 2H y = 2H	2H	27.1	28.4	27.3	28.6	28.8	27.0	28.3	27.3	28.5	28.7			
	3H	27.5	28.7	27.8	28.9	29.1	27.4	28.6	27.7	28.8	29.1			
	4H	27.6	28.7	27.9	29.0	29.2	27.5	28.7	27.8	28.9	29.1			
	6H	27.6	28.7	27.9	28.9	29.2	27.6	28.6	27.9	28.9	29.2			
	8H	27.6	28.6	27.9	28.9	29.2	27.6	28.6	27.9	28.9	29.1			
	12H	27.6	28.6	27.9	28.8	29.1	27.5	28.5	27.9	28.8	29.1			
4H	2H	27.2	28.4	27.5	28.6	28.9	27.2	28.3	27.5	28.6	28.8			
	3H	27.8	28.8	28.1	29.0	29.3	27.7	28.7	28.0	29.0	29.3			
	4H	27.9	28.8	28.3	29.1	29.5	27.9	28.8	28.3	29.1	29.4			
	6H	28.0	28.8	28.4	29.2	29.5	28.0	28.8	28.4	29.1	29.5			
	8H	28.0	28.8	28.4	29.1	29.5	28.0	28.8	28.4	29.1	29.5			
	12H	28.0	28.7	28.5	29.1	29.5	28.0	28.7	28.5	29.1	29.5			
8H	4H	28.0	28.7	28.4	29.0	29.4	27.9	28.6	28.3	29.0	29.4			
	6H	28.1	28.7	28.5	29.1	29.5	28.1	28.7	28.5	29.1	29.5			
	8H	28.1	28.7	28.6	29.1	29.5	28.1	28.7	28.6	29.1	29.5			
	12H	28.2	28.6	28.6	29.1	29.5	28.2	28.6	28.6	29.1	29.5			
12H	4H	27.9	28.6	28.3	29.0	29.4	27.9	28.5	28.3	28.9	29.3			
	6H	28.1	28.6	28.5	29.0	29.5	28.1	28.6	28.5	29.0	29.5			
	8H	28.1	28.6	28.6	29.0	29.5	28.1	28.6	28.6	29.0	29.5			
Variations with the observer position at spacings:														
S = 1.0H		+ 0.7 / - 0.9					+ 0.8 / - 1.0							
1.5H		+ 0.5 / - 0.4					+ 0.6 / - 0.5							
2.0H		+ 1.4 / - 1.4					+ 1.5 / - 1.3							

CIE Pub.117 Corrected 16777 lm Total Lamp Luminous Flux. (8log(F/F0) = 9.8)

C Range: 0 - 360DEG
C Interval: 90.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: chen xue chang
Test Date: 2022-04-12

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System: EVERFINE GO-2000B_V1 SYSTEM V2.0.269
Humidity: 65.0%
Test Distance: 7.100m [K=1.0000]
Remarks:


```

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.269
Humidity:65.0%
Test Distance:7.100m [K=1.0000]
Remarks:

```

ISOCANDELA DIAGRAM

NAME: LED High Bay	TYPE:	WEIGHT:
DIM.: $\phi 260 \times H150\text{mm}$	SPEC.:	SERIAL No.:
MFR.:	SUR.: $\phi 0.26$	PROTECTION ANGLE:




C Range: 0 - 360DEG
C Interval: 90.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: chen xue chang
Test Date: 2022-04-12

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System: EVERFINE GO-2000B_V1 SYSTEM V2.0.269
Humidity: 65.0%
Test Distance: 7.100m [K=1.0000]
Remarks:

AAI Figure

NAME: LED High Bay	TYPE:	WEIGHT:
DIM.: $\phi 260 \times H150\text{mm}$	SPEC.:	SERIAL No.:
MFR.:	SUR.: $\phi 0.26$	PROTECTION ANGLE:




Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
C Interval: 90.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: chen xue chang
Test Date: 2022-04-12

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System: EVERFINE GO-2000B_V1 SYSTEM V2.0.269
Humidity: 65.0%
Test Distance: 7.100m [K=1.0000]
Remarks:

ISOLUX DIAGRAM


NAME: LED High Bay	TYPE:	WEIGHT:
DIM.: $\phi 260 \times H150\text{mm}$	SPEC.:	SERIAL No.:
MFR.:	SUR.: $\phi 0.26$	PROTECTION ANGLE:



C Range: 0 - 360DEG
 C Interval: 90.0DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators: chen xue chang
 Test Date: 2022-04-12

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System: EVERFINE GO-2000B_V1 SYSTEM V2.0.269
 Humidity: 65.0%
 Test Distance: 7.100m [K=1.0000]
 Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 90.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: chen xue chang
Test Date: 2022-04-12

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System: EVERFINE GO-2000B_V1 SYSTEM V2.0.269
Humidity: 65.0%
Test Distance: 7.100m [K=1.0000]
Remarks:

```

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.269
Humidity:65.0%
Test Distance:7.100m [K=1.0000]
Remarks:

```